

SHERWIN INC.

Black Oxide Spray Can

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Black Oxide Spray Can
SDS Number: Black Oxide SC

Revision Date: 6/14/2022

Product Use: NDT inspection magnetic particle

Supplier Details: Sherwin Inc.

5530 Borwick Avenue South Gate, CA 90280

Phone: 562-861-6324

Email: sherwin@sherwininc.com
Internet: www.sherwininc.com

Emergency telephone number:

ChemTel 1-800-255-3924 in U.S.A, Canada, Puerto Rico and US Virgin Islands;

ChemTel +1-813-248-0585 outside U.S.A, Canada, Puerto Rico and US Virgin Islands

ChemTel Brazil: 0-800-591-6042, China: 400-120-0751, India: 000-800-100-4086 and Mexico: 01-800-099-0731

2

HAZARDS IDENTIFICATION

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1 Health, Aspiration hazard, 1

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER GHS Hazard Pictograms:







GHS Hazard Statements:

H222 - Extremely flammable aerosol

H229 - Pressurized container: may burst if heated

H304 - May be fatal if swallowed and enters airways

GHS Precautionary Statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 - Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash ... thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P281 - Use personal protective equipment as required.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P311 - IF exposed or concerned: Call a POISON CENTER/doctor/...

P370 + P378 - In case of fire: Use dry chemical, alcohol resistant foam or dry sand to extinguish.

P403 + P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.



SHERWIN INC.

Black Oxide Spray Can

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
68476-86-8	10-30%	Propane/ Isobutane
64742-47-8	70-90%	Distillates (petroleum), hydrotreated light

4 FIRST AID MEASURES

Inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case

of unconsciousness place patient stably in side position for transportation.

Skin Contact: Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids to facilitate irrigation. Get

immediate medical attention.

Ingestion: Clean mouth with water. Keep respiratory tract clear.

Do NOT induce vomiting or attempt chemical neutralization. If symptoms persist, call a physician.

FIRE FIGHTING MEASURES

Flash Point: > 93 °C (> 200 °F), liquid

Flash Point Method: ASTM D-56

Autoignition Temp: 399-425°C-propanol Lower Explosive Limit: 2%(V) 2-propanol UEL: 13%(V) 2-propanol

Suitable extinguishing agents: Alcohol resistant foam, dry chemical, carbon dioxide

Unusual Fire or Explosion Hazards: Contents under pressure. Extremely flammabel

Special hazards arising from

the substance or mixture: Spray can under pressure. Carbon monoxide and carbon dioxide

Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit

Unsuitable extinguishing media: High volume water jet

Further information: Do not allow run-off from fire-fighting to enter drains or water courses. Use a water spray to cool fully

closed containers.

6

5

ACCIDENTAL RELEASE MEASURES

Personal precautions, protective

equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

Environmental precautions: Do not allow to enter storm sewers/ surface or ground water.

Methods and material for containment

and cleaning up:

Collect liquid in an appropriate container or absorb with an inert material such as

vermiculite, dry sand, or earth; DO NOT use combustible materials. Dispose contaminated material as waste according to item 13.

SDS Number: Black Oxide SC Page: 2 / 6 Revision Date: 6/14/2022



SHERWIN INC.

Black Oxide Spray Can

Ensure adequate ventilation..Place in a chemical waste container.

7 HANDLING AND STORAGE

Handling Precautions: Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other ignition

source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes.

Avoid breathing vapor or mist. Use only outdoors or in a well-ventilated area or with approriate respiratory equipment. Do not swallow. When using do not eat,drink or smoke. (See section 8)

Storage Requirements: Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

Keep containers upright to prevent leakage.

Containers may be hazardous when empty since residue liquid may be present

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Provide adequate ventilation for work and storage areas.

Personal Protective Chemical resistant gloves; Equipment: Chemical safety glasses;

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended

imits.

Where concentrations are above recommended limits, use an organic vapor respirator with dust, mist,

and fume filters; Impervious clothing.

Exposure Limits:

68476-86-8 Propane/butane

USA OSHA TWA/STEL ACGIH TWA/STEL TLV(STEL) 1000 ppm ACGIH

Contains no other substances with occupational exposure limits. The following manufacturere's internal standard would apply: 100ppm (525 mg/m3) for 8-hour

TWA (exposure limit for petroleum distillate - stodard solvent)





General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.



> 93 °C (> 199 °F) (ASTM D-93), liquid

SHERWIN INC.

Black Oxide Spray Can

Flash Point:

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: clear liquid wit hblack particles

Physical State:liquid with particles that settleOdor:HydrocarbonSpec Grav./Density:0.81, liquidSolubility:Not soluble in water

Viscosity: Kinematic at 37.8 °C (100 °F): 2.7 cSts

(ASTM D455), liquid

Boiling Point: 240 °C (464 °F), liquid

Vapor Pressure: < 0.1 mmHg @ 20 °C (68 °F), liquid

pH: Not determined

Evaporation Rate: Not determined

Vapor Density: 6.8, liquid

Auto-Ignition Temp: No data available UFL/LFL: No data available

STABILITY AND REACTIVITY

Reactivity:No dangerous reaction under normal use. **Chemical Stability:**Product is stable under normal conditions.

Conditions to Elevated temperatures

Avoldentification:

10

Materials to Avoldentification: Strong Acids;

Strong Bases

Strong Oxidizing Agents.

Hazardous Decomposition: Carbon oxides, sulphur oxides

Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

Acute Toxicity

Inhalation: LC50: >0.5 mg/l

LC/50 (Rat) (1 hour): >24.1 mg/l

Oral: LC50 Rat: > 5000 mg/kg

Skin corrosion/irritation: Primary irritant.

Serious eye damage/irritation: Primary irritant.

Skin sensitization: No data available

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen for this intended use by IARC.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or antici-pated carcinogen by NTP.

STOT - single exposure: No data available STOT - repaeted exposure: No data available

12 ECOLOGICAL INFORMATION



SHERWIN INC.

Black Oxide Spray Can

Ecotoxcity

Not toxic to aquatic organisms up to the substances water solubility.

Persistency and degradability

No data available.

Bioaccumulative potential

No data available

Mobility

No data available

13

DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable local, state and federal regulations

Empty containers may retain product residue (liquid and/or vapor) and can be dangerous.

14

TRANSPORT INFORMATION

DOT, IATA, IMDG

UN1950, aerosols, flammable, 2.1

15

REGULATORY INFORMATION

TSCA All components are on the Inventory list

US federal regulations

CERCLA Hazardous Substance List (40 CFR 302.4) None

SARA 302: No chemicals in this product are subject to reporting requirements of SARA Title III, Section 302

SARA 304 Emergency release notification: Not regulated.

SARA 311/312 Hazard classes

Flammable (gases, aerosols, liquids, or solids) Aspiration hazard

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting) This product does not contain a chemical listed at or above de minimis concentration



SHERWIN INC.

Black Oxide Spray Can

16

OTHER INFORMATION

NFPA: Health = 2, Fire = 4, Reactivity = 0, Specific Hazard = n/a



This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Author: Sherwin Inc.

Publication Date: June 14, 2022

Revision No. 0

Revision Date: 6/14/2022